



Applications

- High pressure discharge of liquid foodstuffs such as milk, beer, oil, fat, wine, cider, fruit juice, and alcohol up to 70%.
- Suction on unloading bays in dairies.
- Equipment of processing and filling plants, and liquid foodstuff tankers.

Advantages

- Smooth, seamless, white, multi-purpose food grade tube that does not propagate bacterial growth.
- Able to recover its shape after accidental squeeze.
- Changes in temperature have little effect due to the qualities of the rubber compound.
- Resistant to cleaning with detergents at temperatures up to 130 °C (during several minutes).
- Non-marking, abrasion resistant cover.
- International approvals.



ID ≥ 50 mm

Technical description

Inner tube: food grade, oil resistant NBR, white, smooth.





Reinforcement: synthetic textile, braids.

Helix: ID ≥ 50 mm with embedded plastic (PET).

Cover: oil and weather resistant CR, blue, fabric impression.

Temperature range: -30 °C to +100 °C.

Branding: by transfer stripe showing a discontinuous of white trapeziums with:

 TRELLEBORG printed in blue on each trapezium
 and  **ALIKLER D**   printed in white between trapeziums

- in opposite, continuous embossed marking:

 TRELLEBORG - **ALIKLER D - DN - WP 15 bar - week / year**

Standard / approval:

CEE GUIDE for foodstuffs contact.

Directives of the German legislation (BgVV) on sanitary hoses.

Food grade approval from the French Institute of Poitiers (IANESCO).

Couplings / Fittings

Specially designed fittings are available.

Please contact TRELLEBORG for further information in order to get optimum connections.

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Length m	Article No.	Stock item
32.0 -0 / +1	6.0	44.0 ± 1.5	15	40	0.7	220	1.00	20	61567	•
								40	61568	•
38.0 -0 / +1	6.5	51.0 ± 1.5	15	40	0.7	265	1.20	20	61569	•
								40	61570	•
50.0 -0 / +1	8.0	66.0 ± 1.5	15	40	0.7	300	1.97	20	61571	•
								40	61572	•
63.0 -0 / +1	8.0	79.0 ± 1.5	15	40	0.7	450	2.38	20	61373	•
								40	61574	•
75.0 -0 / +1	8.0	91.0 ± 1.5	15	40	0.7	525	2.85	20	61575	•
								40	61576	•
100.0 -0 / +1	8.5	117.0 ± 1.5	15	40	0.7	700	3.81	20	61577	•
								40	61578	•

• = Stock item.