



## Applications

Floor wash down and hot-water cleaning in food processing industries, canneries, dairies, slaughterhouses, etc.

## Advantages

- Very good resistance to high temperatures.
- Smooth for easy handling with light-coloured, non-marking cover.
- Excellent resistance of the cover compound to animal and vegetable grease.
- International approvals.



## Technical description

**Inner tube:** foodstuff quality, oil resistant NBR, white, smooth.

**Reinforcement:** synthetic textile

**Cover:** oil and weather resistant NBR/PVC, blue, smooth.

**Temperature range:** -20 °C to + 95 °C.

**Branding:** with a discontinuous succession of reversed trapeziums printed in white ink, and between each sequence of trapeziums, printed alternately in white ink :



TRELLEBORG

and

- KLENET -



## Standard / approval:

CEE Guide for foodstuffs contact.

Directives of the American (FDA) and German (BGvV) legislation on sanitary hoses

Food grade approval from the French Institute of Poitiers (IANESCO).

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article No.	Stock item
13.4 ± 0.6	3.85	21.1 ± 0.7	10	30	80	0.29	20	60962	●
							40	60961	●
							60	60952	●
							120	60953	●
15.8 ± 0.7	4.10	24.0 ± 0.8	10	30	95	0.35	20	60964	●
							40	60963	●
							60	60954	●
							120	60955	●
19.4 ± 0.7	4.50	28.4 ± 0.8	10	30	115	0.46	20	60966	●
							40	60965	●
							60	60956	●
							25.4 ± 1.0	4.80	35.0 ± 1.1
40	60967	●							
60	60957	●							

● = Stock item.